# Find Your Comfort Zone





### **Energy-Efficient Air Handlers**




#### Fresh Air Comfort, Whatever the Season

Like all Whirlpool® Home Cooling and Heating products, our Air Handlers are designed with your year-round comfort in mind. Working in tandem with an outdoor air conditioner or heat pump, these units quietly and efficiently circulate air throughout the home. Available as complete 1-piece units or as modular 2-piece blowers designed to be paired with a matched coil, sizes range from 1.5–5 tons.













## Whirlpool® WAHMS, WAHME & WAHMV Series 1-Piece Air Handlers

- Air Conditioning & Heat Pump Applications
   Sizes range from 1.5–5 tons. Multi-position for upflow, downflow and horizontal installations.
- Drain Pan with Secondary Connection Allows drainage even when primary pan is plugged; secondary connection provides broader installation options.
- Steel Cabinet with DuraShield™ Coating Offers a low cabinet air leak rating and long-lasting durability that resists scratches and rust.
- Multi-Speed PSC Direct-Drive Motor (WAHMS Series)
   Enables air circulation at multiple speeds for greater comfort and operating efficiency.
- Programmed Multi-Speed EEM Direct-Drive Motor (WAHME Series) Starts softly on low speed while gradually ramping up for reliable, long-term performance and efficiency.
- Variable Speed ECM Direct-Drive Motor (WAHMV Series)

  Starts softly on low speed while gradually ramping up
  to optimal performance. Offers infinite settings for increased
  comfort, quieter operation and energy savings when compared
  to conventional motors.
- Adjustable Airflow Settings (WAHMV Series)
   Optimizes airflow by means of 14 field-selectable settings,
   providing greater operational efficiency and increased comfort.
- Built-in Fan Time Delay Relay
  Increases the SEER rating by optimizing efficiency.
- Auxiliary Electric Heat
  Accepts electric heat kits from 3kw–21kw
  as field-installed options.

## Whirlpool® WMAHM & WMAHV Series 2-Piece Modular Blowers

- Air Conditioning & Heat Pump Applications
   Sizes range from 1.5–5 tons. Multi-position for upflow, downflow and horizontal installations.
- Steel Cabinet with DuraShield™ Coating
  Offers a low cabinet air leak rating and long-lasting durability that resists scratches and rust.
- Foil-Faced Insulated Cabinet Lining
  Helps minimize operating sound and reduce possible cabinet condensation build-up.
- Multi-Speed PSC Direct-Drive Motor (WMAHM Series)
  Enables air circulation at multiple speeds for greater
  comfort and operating efficiency.
- Variable Speed ECM Direct-Drive Motor (WMAHV Series)
  Starts softly on low speed while gradually ramping up
  to optimal performance. Offers infinite settings for increased
  comfort, quieter operation and energy savings when compared
  to conventional motors.
- Built-in Fan Time Delay Relay
   Increases the SEER rating by optimizing efficiency.
- Auxiliary Electric Heat
  Accepts electric heat kits from 3kw–21kw as field-installed options.

#### For customer service, call toll free:

1-866-944-7575, 8 a.m. to 5 p.m. Eastern Time, Monday–Friday. WhirlpoolHVAC-ConsumerSupport@tradewindsHVAC.net



